



Specification

Model	SH-CH-800U1
Dimension Internal (WxDxH)	1000x800x1000(mm) 39.37x31.50x39.37(inch)
Dimension External (WxDxH)	1520x1325x2100(mm) 59.84x52.16x82.67(inch)
Capacity	800 L
Heater Capacity	6 KW
Temp Uniformity	±0.5°C
Temp Range	-25°C ~ 120°C(-13°F~248°F)
Cool Down Time	23°C ~ -20°C (73.4°F~-4°F) About 40min
Heating up Time	-20°C ~ 100°C (-4°F~212°F) About 40min
Temp Controller	Microprocessor Programmable Controller Touch Screen Type
Material Internal	Stainless Steel
Material External	Steel Plate with Powder Heating Coated
Shelves	Movable stainless wire shelves 2 Supplied (31 Maximum)
Temp Accuracy & Stability	±0.1°C
Electrical Requirements 230V,50/60Hz, 3Φ	23.5 A
Weight	395 Kg
Electrical Requirements 380V,50/60Hz, 3Φ	14.0 A

Feature

- Automatic reset function incoming power cut
- Over temp protection
- Electric leakage breaker
- Door open lamp display
- Fan motor over load protection
- Refrigerator over load protection

Option

- Digital recorder
- 2CH Hybrid recorder
- Max temperature 150°C