



Specification

| | |
|-----------------------------|---|
| Model | SH-HD-1900B |
| Type | ClassII A2 |
| Dimension Internal (W×D×H) | 1740×600×750(mm) 68.50×23.62×29.53(inch) |
| Dimension External (W×D×H) | 1900×825×1900(mm) 74.80×32.40×74.72(inch) |
| Control System | Microprocessor LCD Digital Controller |
| Material Internal | Stainless Steel |
| Material External | Steel Plate with Power Heating Coated |
| Utilities | Air&Gas Port |
| Illumination FL Lamp | 32W×1EA |
| Illumination UV Lamp | 36W×1EA |
| UV Time Range | 00.00 to 99HR 59 MIN (MIN SEC) Selectable LCD Counter |

| | |
|-------------------------|---|
| Winding Velocity | 0.2~1.9M/SEC, 10 Step Adjustable |
| Purity | Below to Class 100 |
| Door Type | Tempered Glass by Weight Balance |
| Electrical Requirements | 120V,230V, 1Φ |
| Main Filter | Hepa Filter 0.3μ 99.97% Efficiency Filter |
| Weight | 305 Kg |

Feature

- Fan motor over load Protection
- Automatic reset function incoming power cut
- Buzzer on and UV Lamp cut off when set time arrived
- Emergency stop button

Option

| |
|--|
| |
|--|